

Arrow's kart for Junior classes
using 'low grip' SL tyres



- > 28mm diameter stress relieved chrome moly tubing main chassis structure
- > Removable/adjustable front torsion bar
- > 102cm wheelbase
- > 30mm axle supported by three bearings (40mm axle also available)
- > Arrow's unique machined billet alloy one piece bearing flanges
- > Arrow's unique anti-vibration engine mount
- > Two rear axle ride height settings
- > Ventilated 18mm wide rear brake disc
- > Machined billet alloy two spot caliper
- > Machined billet alloy master cylinder
- > Arrow's unique self-centering seat washers
- > 70mm long machined billet alloy rear wheel hubs
- > 8mm precision ground king-pin bolts
- > Adjustable camber/caster
- > Adjustable front ride height
- > Adjustable Ackerman
- > Machined alloy steering tie rods
- > All aluminium components anodized gunmetal
- > Adjustable engine side seat support bracket
- > 9-litre removable fuel tank
- > Arrow's unique steering bush with clamp for easy wheel alignment
- > Arrow embroidered flat top suede steering wheel
- > Front nosecone, nassa panel and sidepods in black
- > Dynamic Arrow graphics kit
- > One-piece machined alloy 3 spoke wheels; Front - 130mm (5.1") wide x 5" diameter; Rear - 205mm (8") wide x 5" diameter



Features...



Adjustable & removable front torsion bar



Adjustable camber/caster and front ride height



Machined billet alloy brake master cylinder anodised black




Arrow silver/black one-piece machined alloy 3-spoke wheels



Arrow's unique steering bush with clamp for easy wheel alignment



Arrow embroidered flat top suede steering wheel



Arrow's unique self-centering seat washers



30mm axle supported by three bearings (40mm also available)



Machined billet alloy 2-spot brake caliper anodised black



Due to constant development, specifications may change without notice

For full details and specifications visit www.arrowkarts.com

