



Within Australia Ph: 1800 ARROW KARTS

or visit

www.arrowkarts.com

KART SET UP SHEET

Kart Model: X1 CIK

Driver: B. Price

Class: Rotax Light Event: Val Findlay Geelong Date: 16/11/2008

AXLE SIZE: 50mm AXLE LENGTH: 1030mm AXLE TYPE: Soft

- NUMBER OF REAR AXLE BEARINGS: 3
 - FRONT CRASH BAR: TIGHT X LOOSE _____
 - REAR CRASH BAR: TIGHT X LOOSE _____
 - FRONT TRACK: 15 mm OF SPACERS INSIDE WHEEL.
 - REAR TRACK: 1370 mm OVERALL WIDTH TO OUTSIDE EDGE OF WHEELS.
 - FRONT WHEEL ALIGNMENT: ZERO _____ TOE IN _____ mm TOE OUT 2 mm
 - FRONT CASTOR: MINIMUM _____ X _____ CENTRAL _____ MAXIMUM _____
 - FRONT CAMBER: ZERO _____ POSITIVE 4 mm NEGATIVE _____ mm
 - STUB AXLE: INNER _____ OUTER _____
 - TIE ROD MOUNTING HOLE: INNER _____ MIDDLE _____ X _____ OUTER _____
 - SEAT POSITION: A 23 mm B 210 mm C 90 mm
 - SEAT STAYS: TIGHT X LOOSE _____ 2 OR 4? 2
 - SIDE TORSION BAR: IN _____ OUT _____
 - FRONT TORSION BAR / CLAMP: IN _____ OUT _____
 - REAR TORSION BAR: OUT X VERTICAL _____ FLAT _____
 - REAR CIK CROSS BAR: TIGHT X LOOSE _____ REMOVED _____
 - TYRE PRESSURE: FRONT LEFT 14(Cold) FRONT RIGHT 13.5(Cold) PSI OR BAR? PSI
 - TYRE PRESSURE: REAR LEFT 13.5(Cold) REAR RIGHT 13(Cold) PSI OR BAR? PSI
 - WHEEL FRONT TYPE: _____ Douglas Magnesium Solid
 - WHEEL REAR TYPE: _____ Douglas Magnesium Solid
 - FRONT HUB LENGTH: 65MM
 - REAR HUB LENGTH: 90MM
 - SIDE POD BARS: LOOSE _____ TIGHT X
 - FRONT RIDE HEIGHT: LOW X MIDDLE _____ HIGH _____
 - REAR RIDE HEIGHT: LOW _____ MIDDLE _____ X _____ HIGH _____
- OTHER SPECIAL DETAILS: Tyre: Mojo D2 25mm Stub Axles